

KEL 24-E

Extended Cable Entry Frames



V2A anti-corrosive
Also available with stainless steel screws (V2A).



Also available with threaded bushings.

IP54

Description	Type	Order No.	Grommets small large	PU
-------------	------	-----------	---------------------------	----

Product Description

The cable entry frame KEL 24-E offers a larger frame size for routing a greater amount of cables, pipes or conduits.

The KEL24-E series are KEL 24 frames extended with an additional middle frame for routing additional cables. Thus allowing a quick, easy and cost effective routing solution for up to 60 cables.

A flat rubber gasket is included in the shipment.

Advantages & Benefits


- Warranty on pre-terminated cables remains
- Retrofits, repairs and maintenance can be done much more easily and quickly
- High cable density
- Strain relief according to EN 62444
- High stability, vibration resistant

Specifications

Material	Polyamide (PA)
Flame class	UL94-Vo
IP Rating	IP54, with gasket and correct selection of cable grommets (certified acc. to EN 60529)
Temperature	- 40°C to + 140°C (static) - 40°F to + 284°F (static)
Properties	Halogen-free, silicone-free
Cut-out dimensions	66 × 112 mm / Page 192 - 193
Frame depth	17 mm

Accessories

KEL-SNAP Mounting frames	36 - 37
Cable grommets	44 - 48
KEL-EMC Grounding mounts	122 - 124



KEL 24|15-E

42209

15|-


1

KEL 24|15-E
with V2A screws

42209.200

15|-

1



KEL 24|12-E

42208

11|1


1

KEL 24|12-E
with V2A screws

42208.200

11|1

1



KEL 24|9-E

42207

7|2


1

KEL 24|9-E
with V2A screws

42207.200

7|2

1



KEL 24|10-E

49056

10|-

1

KEL 24|10-E
with V2A screws

49056.200

10|-

1