

KEL 24-MT

Extended Cable Entry Frames



V2A
anti-corrosive

Also available with stainless steel screws (V2A).



Also available with threaded bushings.



Type	Order No.	Grommets small large	PU	Description
------	-----------	---------------------------	----	-------------

KEL 24 20-MT	42232	20 -	1	
KEL 24 20-MT with V2A screws	42232.200	20 -	1	
KEL 24 17-MT	42224	16 1	1	
KEL 24 17-MT with V2A screws	42224.200	16 1	1	
KEL 24 14-MT	42225	12 2	1	
KEL 24 14-MT with V2A screws	42225.200	12 2	1	
KEL 24 11-MT	42222	8 3	1	
KEL 24 11-MT with V2A screws	42222.200	8 3	1	
KEL 24 8-MT	42221	4 4	1	
KEL 24 8-MT with V2A screws	42221.200	4 4	1	

Product Description

The cable entry frame KEL 24-MT provides additional cable routing possibilities.

The KEL 24-MT series are KEL frames extended with an additional middle frame for routing additional cables. Thus allowing the quick, easy and cost effective routing solution for up to 80 cables.

A flat rubber gasket is included in the shipment.

Advantages & Benefits

- Warranty on pre-terminated cables remains
- Retrofits, repairs and maintenance can be done much more easily and quickly
- High cable density
- Strain relief according to EN 62444
- High stability, vibration resistant

Specifications

Material	Polyamide (PA)
Flame class	UL94-Vo
IP Rating	IP54, with gasket and correct selection of the cable grommets (certified acc. to EN 60529)
Temperature	- 40°C to + 140°C (static) - 40°F to + 284°F (static)
Properties	Halogen-free, silicone-free
Cut-out dimensions	82 × 112 mm / Page 192 - 193
Frame depth	17 mm

Accessories

KEL-SNAP Mounting frames	36 - 37
Cable grommets	44 - 48
KEL-EMC Grounding mounts	122 - 124