







FT Grommets for Flat Cables



Type	Order No. gray	Clamping range	PU	Description
FT-1 o	46201	Blank grommet	5	
FT-1 A	46210	Width: 19 - 23 mm Thickness: 5.5 - 6 mm	5	
FT-1 B	46211	Width: 28 - 33 mm Thickness: 5.5 - 6 mm	5	
FT-1 C	46212	Width: 24 - 30 mm Thickness: 8.5 - 9 mm	5	
FT-1 E	46214	Width: 19 - 24 mm Thickness: 6.5 - 7 mm	5	
FT-1 F	46215	Width: 28 - 33 mm Thickness: 9 - 9.5 mm	5	
FT-2 o	46202	Blank grommet	5	
FT-2 A	46250	Width: 32.5 - 38 mm Thickness: 5 - 5.5 mm	5	
FT-2 B	46251	Width: 45 - 50.5 mm Thickness: 6 - 6.5 mm	5	
FT-2 C	46252	Width: 47 - 52 mm Thickness: 9.5 - 10 mm	5	
FT-2 F	46255	Width: 38 - 43 mm Thickness: 12.5 - 13 mm	5	
FT-2 G	46256	Width: 49 - 54 mm Thickness: 5 - 6 mm	5	
FT-3 o	46203	Blank grommet	5	
FT-3 A	46300	Width: 72 - 77 mm Thickness: 5 - 5.5 mm	5	
FT-4 o	46204	Blank grommet	5	
FT-4 A	46330	Width: 85 - 99 mm Thickness: 4.2 - 5.2 mm	5	

Product Description

FT grommets are used to route flat cables, e.g. in elevator construction. Suitable for cable entry frames KEL-FL.

Innovative construction of the grommets compensates for manufacturing inconsistencies in flat cables.

Advantages & Benefits

- Routing of flat cables with various dimensions

Specifications

Material	Elastomer
Flame class	UL94-Vo
IP Rating	IP54
Temperature	- 40°C to + 90°C (static) - 40°F to + 194°F (static)
Properties	Halogen-free, silicone-free

Compatible with

KEL-FL Cable entry frames 30