

# KEL-DPZ round Cable Entry Plates



Also available in black.



Membrane on front



Conical shape on back provides additional sealing and strain relief

## Product Description

KEL-DPZ entry plates are designed to route and seal cables without connectors or fiber optics (from 1.5 mm to 22 mm in diameter) in limited space.

The assembly of the KEL-DPZ round with cables or pneumatic hoses can be done quick and easy. Simply make a small hole in the thin membrane, push the cables through. The KEL-DPZ round provides strain relief and protection IP66 / IP67 / IP68 / NEMA type 4X.

The round versions of the KEL-DPZ series have a thread to fit in metric cut-outs from M32 to M63. Thus cut-outs for metric cable glands can be used.

ST-B Plugs can be used for sealing pierced membranes if cables have been removed.

Type	Order No.	Number of cables	Thread metric	External diameter	Mounting height	PU
KEL-DPZ 32 4	<input type="checkbox"/> 43732 <input type="checkbox"/> 50732	3× 3.2 - 6.5 mm 1× 7.2 - 12.5 mm	M32 × 1.5	44 mm	8 mm	10
KEL-DPZ 32 4-2	<input type="checkbox"/> 43733 <input type="checkbox"/> 50733	4× 5 - 9.5 mm	M32 × 1.5	44 mm	8 mm	10
KEL-DPZ 32 7	<input type="checkbox"/> 43734 <input type="checkbox"/> 50734	7× 3.2 - 6.5 mm	M32 × 1.5	44 mm	8 mm	10
KEL-DPZ 40 8	<input type="checkbox"/> 43741 <input type="checkbox"/> 50741	4× 3.2 - 6.5 mm 4× 5 - 10.2 mm	M40 × 1.5	52 mm	8 mm	10
KEL-DPZ 50 8	<input type="checkbox"/> 43750 <input type="checkbox"/> 50750	5× 5 - 10.2 mm 3× 7.2 - 12.5 mm	M50 × 1.5	62 mm	8 mm	10
KEL-DPZ 50 10	<input type="checkbox"/> 43751 <input type="checkbox"/> 50751	7× 3.2 - 6.5 mm 2× 5 - 10.2 mm 1× 16 - 22.2 mm	M50 × 1.5	62 mm	8 mm	10
KEL-DPZ 50 12	<input type="checkbox"/> 43752 <input type="checkbox"/> 50752	4× 3.2 - 6.5 mm 8× 5 - 10.2 mm	M50 × 1.5	62 mm	8 mm	10

\* Only valid for gray product types